

61" 10oz PVC Coated Polyester

- SPECIFICATIONS -

Width	61 inches
Base Fabric (100% Polyester)	1000D x 1000D / 18 x 18
Weight (FS-191-5041)	10 oz / yard ²
Tensile Strength (Grab) (FS-191-5100)	355 lbs x 335 lbs
Tensile Strength (Strip) (FS-191-5102)	265 lbs x 235 lbs
Tear Strength (Tongue) (FS-191-5134)	55 lbs x 55 lbs
Adhesion Strength (FS-191-5970)	10 x 10 lbs / inch
Abrasion Resistance (FS-191-5306)	300 cycles
Hydrostatic Resistance (FS-191-5512)	At least 600 lbs / inch ²
U.V. Resistance (Weather-O-Meter)	Not excessive fading after 300 HRS
Cold Crack Resistance (FS-191-5874)	-40° F
High Temperature Resistance (FS-191-5872)	180° F (Does not Block)
Flame Resistance	Available (Special Order)
Special Treatment(s)	

Disclaimer: These specifications are for general reference. Manufacturing variations may affect the actual performance of the material. To the best of our knowledge and intent these specifications are correct and we strive to maintain stringent quality controls to ensure that you receive what you expect. These specifications do not release the purchaser from their responsibilities in regard to safe handling of these materials. No warranty is implied or expressed.